

PERFORMANCES HYDRAULIQUES TIC-TTS

| ENROULEUR : OPTIMA 1000 DIAMETRE : \varnothing 75 LONGUEUR : 250 M | | | | | | | | REEL MACHINE : OPTIMA 1000 DIAMETER : \varnothing 75 LENGTH : 250 M | | | | | |
|--|---------------------------|-------|----------------------------|--------|----------|---------|---------|---|-------------|------------|----------------------|------------|------------|
| Turbine | ENROULEUR REEL MACHINE | | CANON SR 100 GUN SR 100 | | | | | | | | | | |
| Buse | pression | débit | p. canon | buse | portée | esp. | surface | DOSE EN mm | | | DOSE IN mm | | |
| Nozzle | pressure | flow | p. gun | nozzle | distance | spacing | area | VITESSE EN m/h | | | WINDING SPEED IN m/h | | |
| mm | bar | m3/h | bar | mm | m | m | has | 10 | 20 | 30 | 40 | 50 | 60 |
| 12 | 5.6 /6.7 | 12.2 | 4 | 12,7* | 32.2 | 48 | 1.3 | 25 | 13 | 8 | | | |
| 12 | 6.8 /7.9 | 13.6 | 5 | 12,7* | 34.5 | 54 | 1.5 | 25 | 13 | 8 | | | |
| 12 | 5.9 /7.0 | 15.3 | 4 | 14* | 33.9 | 54 | 1.5 | 28 | 14 | 9 | 7 | | |
| 14 | 7.1 /8.2 | 17 | 5 | 14* | 36.4 | 54 | 1.5 | 31 | 16 | 10 | 8 | 6 | 5 |
| 14 | 5.7 /6.8 | 17.4 | 3.5 | 16 | 34.5 | 54 | 1.5 | 32 | 16 | 11 | 8 | 6 | 5 |
| 14 | 6.3 /7.4 | 18.7 | 4 | 16 | 36 | 54 | 1.5 | 35 | 17 | 12 | 9 | 7 | 6 |
| 16 | 6.9 /8.0 | 19.7 | 4.5 | 16 | 37.5 | 60 | 1.7 | 33 | 16 | 11 | 8 | 7 | 5 |
| 16 | 7.6 /8.7 | 20.8 | 5 | 16 | 38.5 | 60 | 1.7 | 35 | 17 | 12 | 9 | 7 | 6 |
| 16 | 8.2 /9.3 | 21.8 | 5.5 | 16 | 39.5 | 60 | 1.7 | 36 | 18 | 12 | 9 | 7 | 6 |
| 16 | 6.3 /7.4 | 22.4 | 3.5 | 18 | 37 | 54 | 1.5 | 41 | 21 | 14 | 10 | 8 | 7 |
| 16 | 7.0 /8.1 | 23.9 | 4 | 18 | 38.5 | 60 | 1.7 | 40 | 20 | 13 | 10 | 8 | 7 |
| 18 | 7.7 /8.8 | 25.3 | 4.5 | 18 | 40 | 60 | 1.7 | 42 | 21 | 14 | 11 | 8 | 7 |
| 18 | 8.4 /9.5 | 26.6 | 5 | 18 | 41.5 | 66 | 1.9 | 40 | 20 | 13 | 10 | 8 | 7 |
| 18 | 7.2 /8.3 | 28.4 | 3.5 | 20 | 39.5 | 60 | 1.7 | 47 | 24 | 16 | 12 | 9 | 8 |
| NON | 8.0 /9.1 | 30.4 | 4 | 20 | 41.5 | 66 | 1.9 | 46 | 23 | 15 | 12 | 9 | 8 |
| NON | 8.9 /10.0 | 32.6 | 4.5 | 20 | 43 | 66 | 1.9 | 49 | 25 | 16 | 12 | 10 | 8 |
| NON | 9.7 /10.8 | 34.1 | 5 | 20 | 44 | 66 | 1.9 | 52 | 26 | 17 | 13 | 10 | 9 |
| TEMPS D'ENROULEMENT COMPLET EN HEURE TIME FOR COMPLETE WINDING IN HOUR | | | | | | | | 25.0 | 12.5 | 8.3 | 6.3 | 5.0 | 4.2 |

* CANON NELSON SR 100 AVEC BUSE CONIQUE ALU / SR 100 NELSON GUN WITH ALUMINIUM TAPER BORE NOZZLE

26/3/10