

2076 - 2061 VPS - 2076 VPS



SÉRIE 2000 - 2076 EXCELLIUM PACK

This machine can be fitted in two versions: Narrow track or Wide track

SÉRIE 2000 - 2061 VPS ET 2076 VPS EXCELLIUM PACK

Sit down version

| 2076 | |
|------|-------------|
| Ø | 125 - 600 m |
| Ø | 125 - 670 m |
| Ø | 125 - 730 m |
| Ø | 125 - 750 m |

| Hydraulic Performances 2076 - 2076 VPS | | | | | | | | |
|--|-------|------------|-------------------|------|------------------|------------------------|---------------------------|-------------------|
| Model | Ø PE | Length (m) | PE Thickness (mm) | RLL* | Flow rate (m³/h) | Inflow pressure (bars) | Irrigated strip width (m) | Average area (ha) |
| 2076 | Ø 125 | 600 | 14 | 70% | 40 - 76 | 7 - 11 | 72 - 90 | 5,4 |
| | Ø 125 | 670 | 14,0 | 30% | 40 - 72 | 7 - 11 | 72 - 90 | 5,5 |
| | Ø 125 | 730 | 14,0 | 80% | 40 - 70 | 7,5 - 11,5 | 72 - 84 | 6,0 |
| | Ø 125 | 750 | 14,0 | 100% | 40 - 70 | 7,5 - 11,5 | 72 - 84 | 6,2 |

| 2076 VPS | |
|----------|-------------|
| Ø | 125 - 600 m |
| Ø | 125 - 670 m |
| Ø | 125 - 730 m |
| Ø | 125 - 750 m |

| Hydraulic Performances 2061 VPS | | | | | | | | |
|---------------------------------|-------|------------|-------------------|------|------------------|------------------------|---------------------------|-------------------|
| Model | Ø PE | Length (m) | PE Thickness (mm) | RLL* | Flow rate (m³/h) | Inflow pressure (bars) | Irrigated strip width (m) | Average area (ha) |
| 2061 VPS | Ø 125 | 600 | 14,0 | 30% | 40 - 76 | 7 - 11 | 72 - 90 | 5,4 |
| | Ø 125 | 650 | 14,0 | 80% | 40 - 72 | 7 - 11 | 72 - 84 | 5,5 |
| | Ø 135 | 550 | 14,5 | 20% | 40 - 72 | 7,5 - 10 | 72 - 90 | 4,8 |
| | Ø 135 | 600 | 14,5 | 70% | 40 - 72 | 7 - 10,5 | 72 - 90 | 5,3 |

| 2061 VPS | |
|----------|-------------|
| Ø | 125 - 600 m |
| Ø | 125 - 650 m |
| Ø | 135 - 550 m |
| Ø | 135 - 600 m |

| Technical specifications 2076 | | | | | | | | | |
|-------------------------------|-------------|------------|-----------------------|------------------------|------------------------|-----------------|-----------------|-----------|--|
| Model | Height (m.) | Width (m.) | Length ex trolley(m.) | Length in trolley (m.) | Height under frame(m.) | Tyres | Weight ex water | inc water | |
| Optima 2076 | 4,45 | 2,56 | 9,10 | 10,00 | 0,64 | 385 x 65 x 22,5 | 8400 | 13800 | |

| Technical specifications 2061 VPS - 2076 VPS | | | | | | | | | |
|--|------------|----------------|------------|-----------------------|---------------|--------------------|----------------|-----------------|------------------|
| Model | Height (m) | H Sit down (m) | Width (m.) | Length ex trolley (m) | Length in (m) | Height under frame | Tyres | Weight ex water | Weight inc water |
| 2061-2076 VPS | 4,38 | 2,99 | 3,99 | 6,00 | 7,20 | 0,30 | 435 x 55 x R19 | 7200 | 11600 |

*RLL : recovery last layer

EXELLUM PACK



Motor shaft plus synchro



2076 motorization



Dual stabilizers



Disengageable fork head



2076 motorization

SÉRIE 2000 - 2076 EXCELLUM PACK

Standard configuration :

- IRRIDOSEUR Turbine Motorization
- Standard painted version
- Wheels set 400x55x22,5 BKT Flotation 558
- with adjustable track from 1900 to 2300 for narrow track with two high axles 180
- with adjustable track from 2250 to 2700 for wide track with two simple axles
- Part circle gun KOMET Twin 140 ULTRA 24» with nozzles kit 24, 26, 28 et 30 on 125
- Hydraulic stabilizers and lifting trolley.
- Hydraulic front jack.
- Hydraulic lateral distributor.
- Double supply pipe
- Galvanized and articulated trolley with 4 cast iron weights and front wheel
- 3 positions trolley beam
- Rear unwinding system
- Auto shut off valve in standard.
- Hydraulic anchorage of the trolley
- The rear unwinding system and the hydraulic anchorage of the trolley are included in the Pack.

- Double supply pipe, so you can easily connect the reel machine regardless of the turntable rotating adopted.
- Connection hose Ø 100 length 8m and FLD male 5»coupler

Mandatory equipment:

- Motorized butterfly valve: depending on your type of water supply: network or individual pumping, you can either have an automatic valve, a discharge valve, or a dual valve that supports both: automatic and discharge.

Optional equipment:

- Automatic or Discharge valve
- Tyres Options:
 - 550 x 60 x 22,5 - high axle height 180, on wide track, mini way: 2500
 - 315 x 75 x 22,5 - high axle height 180, on wide track, mini way: 2350
 - 315 x 75 x 22,5 - high axle height 180, on narrow track, mini way: 1800
 - mini way: only available with standard tyres
- Gun centring kit for offset trolley
- Trolley guide kit for 2008 series
- Compressor on demand

SÉRIE 2000 - 2061 VPS ET 2076 VPS EXCELLUM PACK

Standard configuration :

- IRRIDOSEUR Turbine Motorization
- Standard painted version
- Part circle gun KOMET Twin 140 ULTRA 24» avec nozzles kit set 24, 26, 28 and 30 on Ø125
- Trolley 4 Wheels and trolley skid included
- Boggie lift, right and left, with individual control system
- Front jack, turntable and stabilizers, automatic trolley locking and trolley hydraulic lift
- Articulated Boggie 4 Wheels 385 X 65 X 22,5
- Connection hose with dispenser Ø 100 length 8m and FLD male 4»coupler

Vps : sit down machine

Mandatory equipment :

- Motorized butterfly valve: depending on your type of water supply: network or individual pumping, you can either have an automatic valve, a discharge valve, or a dual valve that supports both: automatic and discharge.

Optional equipment:

- Autonomous hydraulic system in option